

Addressable Input-Output Devices

W Series

WM221-5 Addressable Input-Output Device

(technical data brief)



The WM221-5 addressable input-output device has 2 inputs, 1 monitored relay output 5A at AC 220V, 5A fuse. The device provides external power AC 220V monitoring. Supplied with a built-in short circuit isolator.

The WM221-5 I/O device is designed to monitor and control smoke removal valves, deluge valves, drencher valves, fire dampers, etc.

Address and input/output mode setting is made during commissioning works via the P-01 device programmer (not included, sold separately).

Technical Data

Operating voltage	17.... 28 V DC
Protocol voltage	5 to 9 V
Quiescent current	≤ 0,25 mA
One LED current consumption	≤ 0,63 mA
All LEDs current consumption (without isolator LED)	1,9 mA
Output relay contact rating	5A at AC 220V
SCI: maximum series resistance - switch closed	≤ 0,13 Ω
Isolator data	Refer to the WM100-2B Short-Circuit Isolator datasheet
Dimensions (L x W x H), mm:	
- WM221-5	103 x 61
- WM221-5B	150 x 94 x 38
- WM221-5D	129 x 94 x 49
Weight	≤ 150 g
Housing IP rating	IP30
Operating temperature	-10 °C to +55 °C
Humidity	up to 95 % (non-condensing)
Average service life	10 years

Available in options:

- WM221-5 - as a printed board to fit in a housing
- WM221-5B – in wall-mount housing
- WM221-5D - in 35 mm DIN rail mount housing

Features

- 2 monitored inputs, 1 monitored output
- Address range 1 – 125
- Built-in short-circuit isolator
- Input, output and SCI status indicators
- Address and input/output mode setting using P-01 device programmer
- Loop powered
- Three mounting type versions
- Easy installation



Ista LLC,
18 Yuriya Matushchaka lane,
Kyiv, Ukraine

Tel.: +380 44 492 30 34,
+380 50 388 94 56
e-mail: info@ista.ua
<https://ista.ua/en/>

